

Chemical Safety Data Sheet MSDS / SDS

ARSENIC PENTASULPHIDE

Revision Date:2026-05-31 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : ARSENIC PENTASULPHIDE
CBnumber : CB3258318
CAS : 1303-34-0
Synonyms : As₂S₃, Arsenic(V) sulfide

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification**GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word Danger

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P391 Collect spillage. Hazardous to the aquatic environment
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazard statements

H410 Very toxic to aquatic life with long lasting effects

SECTION 3: Composition/information on ingredients**Substance**

Product name	: ARSENIC PENTASULPHIDE
Synonyms	: As ₂ S ₃ , Arsenic(V) sulfide
CAS	: 1303-34-0
MF	: As ₂ S ₅
MW	: 310.17

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately.

In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

4.4 Notes to physician

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Arsenic oxides

Not combustible.

Ambient fire may liberate hazardous vapours.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area.

Avoid generation of dusts.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Hygiene measures

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 6.1B: Non-combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

['Component', 'CAS-No.', 'Value', 'Control parameters', 'Basis']	['Arsenic(V) sulfide', '1303-34-0', 'PC-TWA', '0.01 mg/m3', 'Occupational exposure limits for hazardous agents in the workplace - Chemical']	
['', 'Remarks', 'G1 - Carcinogenic to humans', None, None]	['', '', 'PC-STEL', '0.02 mg/m3', 'Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.']	['', '', 'G1 - Carcinogenic to humans', None, None]

hazardous agents.

8.2 Exposure controls

Appropriate engineering controls

Change contaminated clothing. Preventive skin protection recommended. Wash hands after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell,

Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:KCL 741 L

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Material tested:KCL 741 L

Body Protection

protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

a) Physical state	solid
b) Color	brown-yellow amorphous solid
c) Odor	No data available
d) Melting point/freezing point	Melting point/range: > 300 °C
e) Initial boiling point and boiling range	No data available
f) Flammability (solid, gas)	The product is not flammable.
g) Upper/lower flammability or explosive limits	No data available
h) Flash point	Not applicable
i) Autoignition temperature	No data available
j) Decomposition temperature	No data available
k) pH	No data available
l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
m) Water solubility	g/L solution H ₂ O: 0.00136 (0°C) [KRU93]
n) Partition coefficient n-octanol/water	Not applicable for inorganic substances
o) Vapor pressure	No data available
p) Density	No data available
Relative density	No data available
q) Relative vapor density	No data available
r) Particle characteristics	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none
Solubility	insoluble in H ₂ O; soluble in alkaline solutions

9.2 Other safety information

No data available

SECTION 10: Stability and reactivity

10.1 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.2 Possibility of hazardous reactions

No data available

10.3 Conditions to avoid

no information available

10.4 Incompatible materials

Strong oxidizing agents

10.5 Hazardous decomposition products

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute toxicity estimate Oral - 100.1 mg/kg (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Acute toxicity estimate Inhalation - 4 h - 0.501 mg/l - dust/mist (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Dermal: No data available

Skin corrosion/irritation

Classified based on available data. For more details, see section 2

Serious eye damage/eye irritation

Classified based on available data. For more details, see section 2

Respiratory or skin sensitization

Classified based on available data. For more details, see section 2

Germ cell mutagenicity

Classified based on available data. For more details, see section 2

Carcinogenicity

Classified based on available data. For more details, see section 2

Reproductive toxicity

Classified based on available data. For more details, see section 2

Specific target organ toxicity - single exposure

Classified based on available data. For more details, see section 2

Specific target organ toxicity - repeated exposure

Classified based on available data. For more details, see section 2

Aspiration hazard

Classified based on available data. For more details, see section 2

11.2 Additional Information

The following applies to arsenic and its compounds in general: they take effect as capillary and enzyme toxins. Symptoms of arsenic poisoning: acute: after inhalation, mucosal irritations with coughing, dyspnoea, pain in the thorax. Perforations within the respiratory tract are possible. After oral uptake, gastrointestinal disorders with vomiting, diarrhoea, and spasms, CNS disorders with headache, confusion, shaking fits and disturbed consciousness, cardiovascular disorders all the way to circulatory collapse. Chronic: exanthema, dermal lesions in the form of hyperkeratosis and hypermelanosis, loss of hair, conjunctivitis and polyneuropathy, impaired hepatic function, and renal damage. After accumulation in the liver, kidneys, and skin, arsenic is eliminated from the organism only slowly. Experience has shown arsenic compounds to be carcinogenic in man.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1557

IMDG: 1557

IATA-DGR: 1557

14.2 UN proper shipping name

ADR/RID: ARSENIC COMPOUND, SOLID, N.O.S. (Arsenic(V) sulfide)

IMDG: ARSENIC COMPOUND, SOLID, N.O.S. (Arsenic(V) sulfide)

IATA-DGR: Arsenic compound, solid, n.o.s. (Arsenic(V) sulfide)

14.3 Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA-DGR: 6.1

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA-DGR: II

14.5 Environmental hazards

ADR/RID: yes

IMDG Marine pollutant: yes

IATA-DGR: no

14.6 Special precautions for user

Based on chemical properties, choose appropriate tools and conditions of transport.

Transporting tools shall be equipped with appropriate and sufficient firefighting equipment and emergency leaking installations. If transporting by road, please go along the specified route.

14.7 Incompatible materials

Strong oxidizing agents

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Occupational Labor Protection in the at workplaces where Toxic Substances Are Used

Catalogue of Highly Toxic Chemicals : Listed

Measures on the Environmental Administration of New Chemical Substances Registration

Registration/Notification number : B1A222220811

Downstream users need to comply with the conditions of safe use of the chemical, understand the environmental and health hazard and risk management measures identified on the SDS as well as the local/national regulations concerning the chemical.

Other regulations

Please pay attention on the waste treatment should also comply with local regulations requirement.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

TWA: Time-Weighted Average

STEL: Short-Term Exposure Limit

LD50: Lethal Dose 50%

LC50: Lethal Concentration 50%

EC50: Effective Concentration 50%

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

IMDG: International Maritime Dangerous Goods Code

IATA: International Air Transport Association

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

DOT: US Department of Transportation

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.