

Chemical Safety Data Sheet MSDS / SDS

p-Toluidine

Revision Date:2026-06-06 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**Product identifier**

Product name : p-Toluidine
CBnumber : CB8381150
CAS : 106-49-0
EINECS Number : 203-403-1
Synonyms : p-Toluidine,4-Methylaniline

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification**GHS Label elements, including precautionary statements**

Symbol(GHS)



Signal word

Danger

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352 IF ON SKIN: wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P309 IF exposed or if you feel unwell:

P310 Immediately call a POISON CENTER or doctor/physician.

P311 Call a POISON CENTER or doctor/physician.

P342+P311 IF experiencing respiratory symptoms: call a POISON CENTER or doctor/physician.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Hazard statements

H301 Toxic if swallowed

H311 Toxic in contact with skin

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

H331 Toxic if inhaled

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H351 Suspected of causing cancer

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

SECTION 3: Composition/information on ingredients

Substance

Product name	: p-Toluidine
Synonyms	: p-Toluidine,4-Methylaniline
CAS	: 106-49-0
EC number	: 203-403-1
MF	: C7H9N
MW	: 107.15

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Carbon oxides Nitrogen oxides (NO_x) Combustible.

Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air on intense heating.

Development of hazardous combustion gases or vapours possible in the event of fire.


Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



■ HEALTH 3 Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

■ FIRE 2 Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

■ REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

□ SPEC.
□ HAZ.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Keep away from

heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Dry. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril? L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril? L

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

Recommended Filter type: Filter A-(P3)

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

Exposure limits

TLV-TWA skin 2 ppm (~9 mg/m³) (ACGIH); Suspected Human Carcinogen (ACGIH).

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

Appearance	white crystalline
Odour	alcohol-like
Odour Threshold	No data available

pH	at 20 °C alkaline
Melting point/freezing point	Melting point/range: 41 - 46 °C - lit.
Initial boiling point and boiling range	200 °C - lit.
Flash point	87 °C - closed cup - DIN 51758
Evaporation rate	No data available
Flammability (solid, gas)	does not ignite - Flammability (solids)
Upper/lower flammability or explosive limits	6.6%
Vapour pressure	1,3 hPa at 50 °C
Vapour density	3,9
Relative density	0.962
Water solubility	7,5 g/l at 20 °C
Partition coefficient: n-octanol/water	log Pow: 1,39 - (Lit.), Bioaccumulation is not expected.
Autoignition temperature	480 °C - DIN 51794
Decomposition temperature	No data available
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Explosive properties	No data available
Oxidizing properties	No data available

Other safety information

Solubility in other solvents

Ether at 20 °C

soluble Alcohol at 20 °C

soluble

Dissociation constant 5,08 at 25 °C

Relative vapor density

3,9

SECTION 10: Stability and reactivity

Reactivity

Forms explosive mixtures with air on intense heating.

A range from approx. 15 Kelvin below the flash point is to be rated as critical.

The following applies in general to flammable organic substances and mixtures: in correspondingly fine distribution, when whirled up a dust explosion potential may generally be assumed.

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Risk of explosion with:

Nitric acid

Risk of ignition or formation of inflammable gases or vapours with: mineral acids
acids

Conditions to avoid

Strong heating.

Incompatible materials

various plastics

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 620 mg/kg (OECD Test Guideline 401)

Acute toxicity estimate Inhalation - 4 h - 3,1 mg/l (Expert judgment)

Remarks: (Regulation (EC) No 1272/2008, Annex VI) Symptoms: Possible damages:., mucosal irritations

LD50 Dermal - Rabbit - 890 mg/kg Remarks: (RTECS)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit Result: irritating

(OECD Test Guideline 405)

Respiratory or skin sensitization

Patch test: - Guinea pig Result: positive Remarks:

(ECHA)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration. Test system: Chinese hamster lung cells

Metabolic activation: Metabolic activation Method: OECD Test Guideline 473 Result: positive

Test Type: Ames test

Test system: Escherichia coli/Salmonella typhimurium Metabolic activation: Metabolic activation

Method: OECD Test Guideline 471 Result: positive

Species: Mouse Application Route: Oral Remarks: DNA inhibition

Species: Mouse

Application Route: Intraperitoneal Remarks: DNA damage

Carcinogenicity

No data available

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

No data available

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

Toxicity

LD50 orally in Rabbit: 336 mg/kg LD50 dermal Rabbit 890 mg/kg

SECTION 12: Ecological information

Toxicity

Toxicity to fish

LC50 - *Oryzias latipes* (Orange-red killifish) - 120 mg/l - 96 h (OECD Test Guideline 203)

LC50 - *Pimephales promelas* (fathead minnow) - 13,5 - 16,3 mg/l - 96,0 h

Toxicity to daphnia and other aquatic

semi-static test EC50 - *Daphnia magna* (Water flea) - 0,12 mg/l - 48 h

invertebrates (OECD Test Guideline 202)

Toxicity to algae

Growth inhibition ErC50 - *Pseudokirchneriella subcapitata* (green algae) - 24 mg/l - 72 h
(OECD Test Guideline 201)

Growth inhibition NOEC - *Pseudokirchneriella subcapitata* (green algae) - 3,1 mg/l - 72 h
(OECD Test Guideline 201)

Toxicity to bacteria

microtox test EC50 - *Photobacterium phosphoreum* - 4,27 mg/l - 30 min

Remarks: (Lit.)

Persistence and degradability

Biodegradability aerobic - Exposure time 20 d

Result: > 68 % - Readily biodegradable. (OECD Test Guideline 301D)

Biochemical Oxygen Demand (BOD)

1.630 mg/g

Bioaccumulative potential

Mobility in soil

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Toxics Screening Level

The initial threshold screening level (ITSL) for p-Toluidine is 0.03 µg/m³ based on an annual averaging time.

Other adverse effects

Additional ecological information

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Incompatibilities

para-Toluidine is incompatible with oxidizers; contact may cause fires or explosions. Keep away from alkaline materials, strong bases, strong acids, oxoacids, epoxides. May be incompatible with isocyanates, halogenated organics, peroxides, phenols (acidic), epoxides, anhydrides, and acid halides. Flammable gaseous hydrogen is generated in combination with strong reducing agents, such as hydrides.

Waste Disposal

Consult with environmental regulatory agencies for guidance on acceptable disposal practices. Generators of waste containing this contaminant (≥ 100 kg/mo) must conform with EPA regulations governing storage, transportation, treatment, and waste disposal. Controlled incineration (oxides of nitrogen are removed from the effluent gas by scrubbers and/or thermal devices).

SECTION 14: Transport information

UN number

ADR/RID: 3451 IMDG: 3451

UN proper shipping name

ADR/RID: TOLUIDINES, SOLID IMDG: TOLUIDINES, SOLID IATA: Toluidines, solid

Transport hazard class(es)

ADR/RID: 6.1 IMDG: 6.1

Packaging group

ADR/RID: II IMDG: II IATA: II

Environmental hazards

ADR/RID: yes IMDG Marine pollutant: yes IATA: no

Special precautions for user

No data available

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015: Listed. website: <https://www.mem.gov.cn/>

Measures for Environmental Management of New Chemical Substances

New Zealand Inventory of Chemicals (NZIoC):Listed. website: <https://www.epa.govt.nz/>

EC Inventory:Listed.

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: <https://echa.europa.eu/>

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: <https://www.epa.gov/>

Vietnam National Chemical Inventory:Listed. website: <https://chemicaldata.gov.vn/>

Korea Existing Chemicals List (KECL):Listed. website: <http://ncis.nier.go.kr>

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: <https://www.mee.gov.cn/>

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: <https://emb.gov.ph/>

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

[1] CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>

[2] ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>

[3] ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

[4] eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

[5] ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>

[6] Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>

[7] HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>

[8] IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>

[9] IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>

[10] Sigma-Aldrich, website: <https://www.sigmaaldrich.com/>

Other Information

Depending on the degree of exposure, periodic medical examination is suggested. Specific treatment is necessary in case of poisoning with this substance; the appropriate means with instructions must be available. The odour warning when the exposure limit value is exceeded is insufficient. Do NOT take working clothes home. See ICSCs 0341 and 0342.

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.