

Chemical Safety Data Sheet MSDS / SDS

Tributylamine

Revision Date:2026-05-30 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name : Tributylamine
CBnumber : CB5124462
CAS : 102-82-9
EINECS Number : 203-058-7
Synonyms : TBA,tributylamine

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : For R&D use only. Not for medicinal, household or other use.
Uses advised against : none

Company Identification

Company : Chemicalbook
Address : Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
Telephone : 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

Symbol(GHS)



Signal word

Danger

Precautionary statements

P314 Get medical advice/attention if you feel unwell.
P301+P312 IF SWALLOWED: call a POISON CENTER or doctor/physician IF you feel unwell.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P262 Do not get in eyes, on skin, or on clothing.

Hazard statements

H372 Causes damage to organs through prolonged or repeated exposure
H315 Causes skin irritation
H302 Harmful if swallowed

SECTION 3: Composition/information on ingredients

Substance

Product name	: Tributylamine
Synonyms	: TBA,tributylamine
CAS	: 102-82-9
EC number	: 203-058-7
MF	: C12H27N
MW	: 185.35

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

4.4 Notes to physician

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Nitrogen oxides (NO_x)

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air on intense heating.


Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



HEALTH 3 Short exposure could cause serious temporary or moderate residual injury (e.g. [liquid hydrogen](#), [sulfuric acid](#), [calcium hypochlorite](#), hexafluorosilicic acid)

FIRE 2 Must be moderately heated or exposed to relatively high ambient temperature before ignition can occur and multiple finely divided suspended solids that do not require heating before ignition can occur. Flash point between 37.8 and 93.3 °C (100 and 200 °F). (e.g. diesel fuel, [sulfur](#))

REACT 0 Normally stable, even under fire exposure conditions, and is not reactive with water (e.g. helium, [N₂](#))

SPEC.

HAZ.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-

absorbent material (e.g.

Chemizorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

hygroscopic

Storage class

Storage class (TRGS 510): 6.1A: Combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL)

['Application Area', 'Routes of exposure', 'Health effect', 'Value']
--

Predicted No Effect Concentration (PNEC)

['Sea water', '0.00036 mg/l']	['Fresh water', '0.0036 mg/l']	['Sea sediment', '1.69 mg/kg']	['Fresh water sediment', '16.9 mg/kg']	['Sewage treatment plant', '100 mg/l']	['Aquatic intermittent release', '0.036 mg/l']
----------------------------------	-----------------------------------	-----------------------------------	---	---	---

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 480 min

Material tested: Camatril® (KCL 730 / Aldrich Z677442, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 30 min

Material tested: Butoject® (KCL 898)

Body Protection

protective clothing

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

Information on basic physicochemical properties

a) Physical state	clear, liquid
b) Color	colorless
c) Odor	unpleasant
d) Melting point/freezing point	Melting point/range: -70 °C - lit.
e) Initial boiling point and boiling range	216 °C - lit.
f) Flammability (solid, gas)	No data available
g) Upper/lower flammability or explosive limits	Upper explosion limit: 6 %(V) Lower explosion limit: 1.4 %(V)
h) Flash point	63 °C - closed cup
i) Autoignition temperature	210 °C at 1,015 hPa - DIN 51794
j) Decomposition temperature	No data available
k) pH	10.2 at 0.1 g/l at 25 °C - DIN 19268

l) Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 1.4 mPa.s at 20 °C - ASTM D 445
m) Water solubility	0.08 g/l at 20 °C - OECD Test Guideline 105- slightly soluble
n) Partition coefficient n-octanol/water	log Pow: 3.338 at 25 °C - Bioaccumulation is not expected.
o) Vapor pressure	3.2 hPa at 55 °C
p) Density	0.777 g/cm ³ at 25 °C - lit.
Relative density	0.778 g/mL at 25 °C(lit.)
q) Relative vapor density	6.38 (vs air)
r) Particle characteristics	No data available
s) Explosive properties	No data available
t) Oxidizing properties	none
Solubility	sparingly soluble in water; soluble in most organic solvents; soluble in acetone and benzene; very soluble in alcohol and ether
Dielectric constant	2.29

9.2 Other safety information

Surface tension

55 mN/m at 0.07g/l at 20 °C - OECD Test Guideline 115

Dissociation constant 10.89 at 25 °C - OECD Test Guideline 112

Relative vapor density

6.4 - (Air = 1.0)

SECTION 10: Stability and reactivity

10.1 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

10.2 Possibility of hazardous reactions

Caution! In contact with nitrites, nitrates, nitrous acid possible liberation of nitrosamines!

Violent reactions possible with:

Oxidizing agents peroxi compounds acids

Risk of explosion with:

Mercury

10.3 Conditions to avoid

Avoid moisture.

Strong heating.

10.4 Incompatible materials

Aluminum, bronze, Copper, brass, Zinc

10.5 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male - 420 mg/kg

Remarks: (ECHA)

Symptoms: After swallowing: irritations of mucous membranes in the mouth, pharynx, oesophagus and gastrointestinal tract., Risk of perforation!, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of vomit.

LC50 Inhalation - Rat - male and female - 4 h - 0.5 mg/l - vapor (OECD Test Guideline 403)

Symptoms: Irritation symptoms in the respiratory tract., Possible damages:, Lung edema,

Symptoms may be delayed.

LD50 Dermal - Rabbit - male - 195 mg/kg

Remarks: (ECHA)

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin. - 4 h (OECD Test Guideline 404)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation (OECD Test Guideline 405)

Respiratory or skin sensitization

Buehler Test - Guinea pig

Result: negative (US-EPA)

Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Micronucleus test

Species: Mouse

Cell type: Red blood cells (erythrocytes)

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Classified based on available data. For more details, see section 2

Reproductive toxicity

Classified based on available data. For more details, see section 2

Specific target organ toxicity - single exposure

Classified based on available data. For more details, see section 2

Specific target organ toxicity - repeated exposure

Classified based on available data. For more details, see section 2

Aspiration hazard

Classified based on available data. For more details, see section 2

11.2 Additional Information

RTECS: YA0350000

CNS stimulation.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

SECTION 12: Ecological information

12.1 Toxicity

No data available

Toxicity to daphnia semi-static test EC50 - Daphnia magna (Water flea) - 8 mg/l - 48 h and other aquatic (OECD Test Guideline 202) invertebrates

Toxicity to algae static test ErC50 - Pseudokirchneriella subcapitata - 10.1 mg/l - 72 h (OECD Test Guideline 201)

Toxicity to bacteria static test NOEC - Bacteria - 100 mg/l - 2 h

Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 88 % - Readily biodegradable.

(OECD Test Guideline 301B)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 28 d - 0.1 mg/l(Tris-n-butylamine)

Bioconcentration factor (BCF): 7.3 (OECD Test Guideline 305)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Endocrine disrupting properties

No data available

12.7 Other adverse effects

Biological effects:

Harmful effect due to pH shift. Forms corrosive mixtures with water even if diluted.

Discharge into the environment must be avoided.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 2542

IMDG: 2542

IATA-DGR: 2542

14.2 UN proper shipping name

ADR/RID: TRIBUTYLAMINE

IMDG: TRIBUTYLAMINE

IATA-DGR: Tributylamine

14.3 Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA-DGR: 6.1

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA-DGR: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA-DGR: no

14.6 Special precautions for user

Based on chemical properties, choose appropriate tools and conditions of transport.

Transporting tools shall be equipped with appropriate and sufficient firefighting equipment and emergency leaking installations. If transporting by road, please go along the specified route.

14.7 Incompatible materials

Aluminum, bronze, Copper, brass, Zinc

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Listed

Other regulations

Please pay attention on the waste treatment should also comply with local regulations requirement.

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

TWA: Time-Weighted Average

STEL: Short-Term Exposure Limit

LD50: Lethal Dose 50%

LC50: Lethal Concentration 50%

EC50: Effective Concentration 50%

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

IMDG: International Maritime Dangerous Goods Code

IATA: International Air Transport Association

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

DOT: US Department of Transportation

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety and Health Administration

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.